



205.W36-U0

WALL BOX CABLE+SOCKET T2

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V
3P+N+E IP54 IK08 Type 2 4m

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	BE-W Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Type of product	WALL BOX CABLE+SOCKET T2	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Synthetical description	WALL BOX CABLE+SOCKET T2	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material	ENGINEERING PLASTIC	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW		
With integrated cable	Type 2		
Cable length	4m		
Cable section	5G6+1x0,5mm ²		
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		

Mounting version	SURFACE MOUNTING
Dimensions	235x370x115mm