

# **PRODUCT DATASHEET**FLOODLIGHT LED 150 W 6500 K BK

# **LEDVANCE FLOODLIGHT LED | LED floodlight luminaires**



#### **AREAS OF APPLICATION**

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

#### **PRODUCT BENEFITS**

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

#### **PRODUCT FEATURES**

- Luminaire efficacy: up to 100 lm/W

- Beam angle: 100°

- Type of protection: IP65



# **TECHNICAL DATA**

### Electrical data

| Nominal wattage | 150.00 W                      |
|-----------------|-------------------------------|
| Operating mode  | Electronic control gear (ECG) |
| Nominal voltage | 220240 V                      |
| Mains frequency | 50/60 Hz                      |


# Photometrical data

| Color temperature                    | 6500 K        |
|--------------------------------------|---------------|
| Luminous flux                        | 15000 lm      |
| Luminous efficacy                    | 100 lm/W      |
| Standard deviation of color matching | ≤5 sdcm       |
| Light color (designation)            | Cool Daylight |
| Color rendering index Ra             | ≥80           |

# Light technical data

| Beam angle | 100.00 ° |
|------------|----------|
|            |          |

# Dimensions & weight



| Length         | 298.0 mm  |
|----------------|-----------|
| Width          | 269.0 mm  |
| Height         | 128.0 mm  |
| Product weight | 5130.00 g |
| Cable length   | 1000 mm   |

# Colors & materials


| Body material | Aluminum |
|---------------|----------|
| Housing color | Black    |
| Product color | Black    |


| Cover material                         | Glass           |  |  |
|--|-----------------|--|--|
| Temperatures & operating conditions    |                 |  |  |
| Ambient temperature range              | -2050 °C        |  |  |
| Lifespan                               |                 |  |  |
| Lifespan L70 at 25 °C                  | 50000 h         |  |  |
| Lifespan L80 at 25 °C                  | 40000 h         |  |  |
| Lifespan L90 at 25 °C                  | 20000 h         |  |  |
| Number of switching cycles             | 30000           |  |  |
| Additional product data                |                 |  |  |
| Mounting type                          | Surface         |  |  |
| Mounting location                      | Wall / Floor    |  |  |
| Capabilities                           |                 |  |  |
| Dimmable                               | No              |  |  |
| Type of connection                     | Cable, 3-pole   |  |  |
| LED module replaceable                 | Not replaceable |  |  |
| Certificates & standards               |                 |  |  |
| Protection class IK (shock resistance) | IK08            |  |  |
| Photobiological safety group EN62778   | RG 0            |  |  |
| Protection class                       | I I             |  |  |
| Type of protection                     | IP65            |  |  |

CE/CB/TÜV SÜD/EAC/RoHS

Standards

### **Light Distribution**





LDC typ cone LDC typ polar

### **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075811027 | Shipping carton box<br>1     | 378 mm x 323 mm x 172 mm             | 5866.00 g    | 21.00 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.