


BQ11FB03C0-MB3-

Price

Lead time

Configuration

Type:	B
Size:	Q11
Input:	Metric
Output shaft/bore:	Standard ø42
Mounting:	FB
Mounting position:	B3
Input bore:	-
Coupling:	-



Technical data

Input rpm (n_1):	n.a. min⁻¹
Output rpm (n_2):	n.a. min⁻¹
Ratio (i):	16.00
Nominal power (P_{1R}):	6.00 kW
Nominal torque (M_{2R}):	536 Nm
Dynamic efficiency (RD):	82%

Selection

Motor power (P_{1M}):	n.a.
Output torque (M_{2M}):	n.a.
Service factor (f.s.):	n.a.


Lubrication

Oil quantity:	2.00l
AGIP:	Blasia 460

On our website


Features	Irreversibility
How to order	Thermal limit
Dimension	Atex certification
Accessories/options	Installation check list
Electric motors	Spare parts list
Selection guide - fs	Complete catalogue
Mounting pos. - lubricant	Selection by power (xls)
Calc. the overhung load	

Direction of rotation



Axial and radial loads


Input shaft



n_2 (min ⁻¹)	FA (N)	FR (N)
1400	228	1140

*Strong axial loads in the DX direction are not allowed

Output shaft



n_2 (min ⁻¹)	FA (N)	FR (N)
200	600	2900
150	700	3300
100	750	3600
75	800	4000
50	920	4600
25	1200	6000
15	1400	7000

Note


Square - Gear
651Nm **Q1 1**

3D dimensions on the Web


PQ11**FB**... Basic wormbox
Riduttore base

M. flanges	Kit code	ϕF	A
71B5	K023.4.041	160	136
80/90B5	K023.4.042	200	138
100/112B5	K023.4.043	250	147
132B5	-	300	187
80B14	K085.4.046	120	138
90B14	K085.4.045	140	138
100/112B14	K023.4.041	160	136
132B14	-	200	187

Gearbox weight peso riduttore	35.0 kg
---	----------------




PQ11**FC**... Output flange
Flangia uscita




type B	øD	E	G	L	N	O	P	Q	kit code
FC	170 ^{+0.083} _{+0.043}	11	16.5	131.5	54	230	270	13	① K110.9.010 ② -
FL	170 ^{+0.083} _{+0.043}	11	16.5	179.5	102	230	270	13	① K110.9.011 ② -

PQ11**F1**... Output flange
Flangia uscita




type S	øD	E	G	L	N	O	P	Q	kit code
F1	180 ^{+0.040} ₀	5	18	150	72.5	215	250	15	① KS110.9.014 ② -
F2	170 ^{+0.083} _{+0.043}	9.5	15	178	100.5	230	270	13	① KS110.9.012 ② -
F3	180 ^{+0.040} ₀	5	18	130	52.5	215	250	15	① KS110.9.013 ② -


PQ11FB...	Feet
	Piedini



PQ11 BR ...	Reaction arm Braccio di reazione
--------------------	-------------------------------------




R Q11FB...	Input shaft Albero in entrata
-------------------	----------------------------------




	ød	e	g	l	m	x	kit code
type B	25 h6	28	8	50	131.5	M8x20	① K085.5.007 PAM90 ② K085.5.008 PAM100
type S	24 h6	27	8	50	131.5	M8x20	① KS085.5.009 PAM90 ② KS085.5.011 PAM100

PQ11.....**S**... Single Shaft
Albero lento semplice



① kit cod. K110.5.028 type B

PQ11.....**D**... Double Shaft
Albero lento bisp.



② kit cod. K110.5.029 type B

[illegible]