



Caracteristici Principale

Functie de comutare	Intermediar
Gama	Asfora
Tip produs sau componenta	Comutator
Prezentare dispozitiv	Produs complet
Tip de sarcina	Load for energy saving lamps with ballast : 100 W
Tenta de culoare	Alb
Tip de ambalaj	Ambalat individual in folie de plastic

Complementare

Numarul clapetei	1
Montare dispozitiv	Incastrat
Gama de puteri	2300 W
Curent nominal	10 AX 250 V AC
Conexiuni - borne	Borna fara surub
Numar de cabluri	2 x 2.5 mm ²
Rigiditate cablu	Flexibil Rigid Impletit solid
Lungime de dezizolare conductor	13 mm
Material	ABS (nitril acrilic butadiena - stirena)
Finisaj suprafata	Glossy
Material conductor	Cupru
Mod de fixare	Screws or claws 51...70 mm
Inaltime	83 mm
Latime	83 mm
Adancime	43 mm
Adancimea proiectata	15 mm
Greutate produs	0.0738 kg

Mediu

standarde	SR EN 60669-1
certificari produs	TSE VDE
etichete privind calitatea	CE 0
grad de protectie IP	IP20
temperatura ambianta pentru utilizare	-5...40 °C

Durabilitatea ofertei

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1834 - Schneider Electric declaration of conformity
REACH	Referinta nu contine SVHC peste prag
Profil de mediu pentru produs	Disponibil
Instructiuni sfarsit de viata produs	Nu necesita operatii specifice de reciclare

Contractual warranty

Perioda	18 luni
---------	---------