



Caracteristici Principale

Gama	Asfora
Tip produs sau componenta	Priza
Descriere priza standard	Legare la pamant laterala
Configuratie poli priza	2P + E
Prezentare dispozitiv	Produs complet
Informatii suplimentare priza	Capac
Tenta de culoare	Alb
Tip de ambalaj	Ambalat individual in folie de plastic

Complementare

Numar priza	1
Montare dispozitiv	Incastrat
Gama de puteri	3680 W
Curent nominal	16 A 250 V c.a.
Conexiuni - borne	Borne lift
Numar de cabluri	2 x 2.5 mm ²
Rigiditate cablu	Flexibil Rigid Impletit solid
Lungime de dezizolare conductor	13 mm
Material	ABS (nitril acrilic butadiena - stirena): rama de capac ABS (acrylonitrile butadiene-styrene) : lid ABS + PC : central plate
Finisaj suprafata	Glossy
Material conductor	Cupru
Mod de fixare	Screws or claws 51...69 mm
Inaltime	83 mm
Latime	83 mm
Adancime	47 mm
Adancimea proiectata	15 mm
Cantitate per set	1
Greutate produs	0.085 kg

Mediu

standarde	IEC 60884-1
certificari produs	TSE VDE
grad de protectie IP	IP20

Durabilitatea ofertei

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1834 - Schneider Electric declaration of conformity
REACH	Referinta nu contine SVHC peste prag
Profil de mediu pentru produs	Disponibil
Instructiuni sfarsit de viata produs	Nu necesita operatii specifice de reciclare

Contractual warranty

Perioada	18 luni
----------	---------